


# Dielectric Slab

(Harrington p. 168; Balanis p. 414)



We first select a set of modes/fields in each region that satisfy the wave equation. You could, of course, use vector potential as before, but we are skipping this step.

**Even fields** ( $H_z$  fields: TM case)

$$H_z^I = B e^{-fx} \cosh(g_1 y)$$

$$H_z^{II} = A e^{-fx} e^{-g_2 y}$$

$f$  is the same for both fields because  $H_z^I = H_z^{II}$  for all  $x$  (like Snell's law). *Note:*

$$\sin j\alpha = j \sinh \alpha$$

$$\cos(\alpha) = \cosh j\alpha$$

$E$ -fields:

$$\begin{aligned} \mathbf{E} &= \frac{1}{j\omega\epsilon} \nabla \times \mathbf{H} = \frac{\nabla \times (\hat{z} H_z)}{j\omega\epsilon} \\ &= -\frac{\hat{z} \times \nabla H_z}{j\omega\epsilon} = -\frac{1}{j\omega\epsilon} \left( \hat{y} \frac{\partial H_z}{\partial x} - \hat{x} \frac{\partial H_z}{\partial y} \right) \\ E_x^I &= B g_1 e^{-fx} \sinh(g_1 y) \frac{1}{j\omega\epsilon_1} \\ E_x^{II} &= -A g_2 e^{-fx} e^{-g_2 y} \frac{1}{j\omega\epsilon_0} \end{aligned}$$

To determine the amplitude constants ( $A, B$ ) and the propagation constants  $g_1, g_2$  and  $f$ , we resort to the application of boundary condition. We have

$$\begin{aligned} H_z^I &= H_z^{II} \Rightarrow 1. \quad \boxed{A e^{-g_2 t} = B \cosh g_1 t} \\ E_x^I &= E_x^{II} \Rightarrow 2. \quad \boxed{A \epsilon_1 g_2 e^{-g_2 t} = -g_1 B \sinh g_1 t} \end{aligned}$$

Also, from the wave equation

$$\begin{aligned} \nabla^2 H_z^{I,\Pi} + \beta^2 H_z^{I,\Pi} &= 0 \Rightarrow \\ 3. \quad &\boxed{g_1^2 = -\underbrace{\beta_0^2 \epsilon_r \mu_r}_{\beta_2^2} - f^2} \Rightarrow \\ &g_1^2 = -\beta_0^2 - \beta_0^2 \epsilon_r \mu_r + g_2^2 \\ &\boxed{g_2^2 = +\beta_0^2 \epsilon_r \mu_r - \beta_0^2 + g_1^2} \\ 4. \quad &\boxed{g_2^2 = -\beta_0^2 - f^2} \end{aligned}$$

For convenience we will take the ratio to eliminate  $A/B$ :

$$\begin{aligned} \frac{E_x^I}{H_z^I} &= \frac{E_x^{\Pi}}{H_z^{\Pi}} = Z_{-y} \\ \hat{x} \times \hat{z} &= -\hat{y} \end{aligned}$$

where  $Z_{-y}$  represents the impedance of a wave traveling along the  $-\hat{y}$  direction at  $y = \pm t$ . This gives the equation

$$\boxed{g_1 \tanh(g_1 t) + \epsilon_r g_2 = 0}$$

or alternatively ( $\tilde{g}_1 = jg_1$ )

$$\boxed{\tilde{g}_1 t \tan(\tilde{g}_1 t) = \epsilon_r t g_2}$$

*Note:*

$$\sin ju = j \sinh u$$

$$\cos ju = \cosh u$$

$$\tan ju = j \tanh u$$

$$\tanh ju = j \tan u$$

**Odd modes** ( $H_z$  fields: TM case)

$$H_z^I = B e^{-fx} \sinh(g_1 y)$$

$$H_z^{\Pi} = A e^{-fx} e^{-g_2 y}$$

and in this case the characteristic equation is

$$\begin{aligned} &g_1 \coth(g_1 t) - \epsilon_r g_2 = 0 \\ \Rightarrow &\boxed{\tilde{g}_1 \cot(\tilde{g}_1 t) = -\epsilon_r g_2, \text{ with } \tilde{g}_1 = jg_1} \end{aligned}$$

*Note:*

$$\cot(ju) = -j \coth u$$

$$\coth(ju) = -j \cot u$$




Figure 3. Graphical solution of the characteristic equation for the slab waveguide.




Figure 6. Contours of constant surface wave loss and velocity for an impedance plane.