


Some questions answered

(1)

- 1) How are modes excited
- 2) How is cut-off frequency (or cut-off wavelength) in a waveguide determined
- 3) Velocity computation



TM modes

$$E_x = \sum_{n=0}^{\infty} A_n \sin\left(\frac{n\pi}{z_1} z\right) e^{-\gamma x} = \sum_{n=0}^{\infty} A_n E_n x$$

$k_z = \frac{n\pi}{z_1}$, $\gamma = jk_x$

n th Mode

From

$$\nabla^2 E_x + k_0^2 E_x = 0 \Rightarrow \boxed{k_x^2 + k_z^2 = k_0^2}$$

Characteristic Equ.

$$k_0 = \frac{2\pi}{\lambda_0} = \omega \sqrt{\mu_0 \epsilon_0} = 2\pi f_0 \sqrt{\mu_0 \epsilon_0}$$

free space wavelength

$$-\gamma^2 + \left(\frac{n\pi}{z_1}\right)^2 = k_0^2$$

- 2) Cut-off frequency & wavelength for the mode
- The modes propagate when $\gamma < 0$ or when k_x is real
- Noting that $\rightarrow k_x = \sqrt{k_0^2 - k_z^2} = \sqrt{k_0^2 - \left(\frac{n\pi}{z_1}\right)^2} = \sqrt{\left(\frac{2\pi}{\lambda_0}\right)^2 - \left(\frac{n\pi}{z_1}\right)^2}$
- the mode begins to propagate when $k_x = 0^+$, i.e. as soon as k_x exceeds zero.

Setting $\gamma = k_x = 0$, we get

$$\frac{2\pi}{\lambda_0} = \frac{n\pi}{Z_1} \Rightarrow \boxed{\lambda_0 = \frac{2Z_1}{n}}$$

or

$$\omega_0 \sqrt{\mu_0 \epsilon_0} = \frac{n\pi}{Z_1} \Rightarrow \omega_0 = \frac{n\pi}{Z_1} \frac{1}{\sqrt{\mu_0 \epsilon_0}}$$

$$\boxed{f_0 = \frac{n}{2Z_1} \frac{1}{\sqrt{\mu_0 \epsilon_0}}}$$

replace with $\frac{1}{\sqrt{\mu_0 \epsilon_0}}$ if the guide is filled with dielectric

$$v_0 = \frac{1}{\sqrt{\mu_0 \epsilon_0}} = c = \text{speed of light}$$

We refer to the above wavelength and frequency as the cut-off wavelengths/frequencies

$$\boxed{\lambda_{oc} = \frac{2Z_1}{n}}$$

$$\text{or } \boxed{Z_1 = n \frac{\lambda_{oc}}{2}}$$

$$\boxed{f_{oc} = \frac{n}{2Z_1} \frac{1}{\sqrt{\mu_0 \epsilon_0}}} \rightarrow \frac{n}{2Z_1} \frac{1}{\sqrt{\mu_0 \epsilon_0}}$$

if the guide is filled with another material

If the operating frequency is

$$f_0 > f_{oc} \text{ or } \lambda_0 < \lambda_{oc} \quad \left(\lambda = \frac{0.3}{f \text{ GHz}} \right)$$

then the mode will propagate. Else the mode will have $\gamma > 0$ and will be attenuated and "die-off" soon after the excitation probe ^{it leaves}

3) Note that $\gamma = jk_x = j\beta \rightarrow j\beta_{\text{guided}} = j\beta_z = j\sqrt{\left(\frac{2\pi}{\lambda_0}\right)^2 - \left(\frac{2\pi}{\lambda_{oc}}\right)^2}$

$$= j\frac{2\pi}{\lambda_0} \sqrt{1 - \left(\frac{\lambda_0}{\lambda_{oc}}\right)^2}$$

$$V_{\text{guided}} = V_{\text{phase}} = \frac{\omega_0}{\beta} = \frac{\frac{2\pi}{\lambda_0} \frac{1}{\sqrt{\mu_0 \epsilon_0}}}{\frac{2\pi}{\lambda_0} \sqrt{1 - \left(\frac{\lambda_0}{\lambda_{oc}}\right)^2}} \Rightarrow V_g = \frac{1}{\sqrt{\mu_0 \epsilon_0} \sqrt{1 - \left(\frac{\lambda_0}{\lambda_{oc}}\right)^2}}$$